



| | | |
|--|-----------|------|
| UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: Unless otherwise specified ANGULAR: MACH ± 1° TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005 | NAME | DATE |
| | DRAWN | DL |
| | CHECKED | |
| | ENG APPR. | |
| | MFG APPR. | |
| INTERPRET GEOMETRIC TOLERANCING PER: | Q.A. | |

Lilja Precision Rifle Barrels, Inc.
P.O. Box 372, Plains, MT 59859
406-826-3084
www.riflebarrels.com

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Lilja Precision Rifle Barrels, Inc. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Lilja Precision Rifle Barrels, Inc. IS PROHIBITED.

MATERIAL
416 Stainless Steel

FINISH
DO NOT SCALE DRAWING

Note: calculated weight shown at lower right, is for a .22 rim fire groove diameter at full length. Shorter lengths and fitting will reduce weight.

| | | |
|------------------------|---------------------|--------------|
| SIZE A | DWG. NO. anscite | REV |
| WEIGHT IN POUNDS: 5.25 | | SHEET 1 OF 1 |